

SPECIFICACIONES

Model number	DJ-581ET
Dehumidify capacity	58L/day (T:30 °C /80%RH)
Supply Voltage	220V/50Hz
Power Consumption	850W
Current draw	3.9Amps
Circulating air flow	600m3/h
Humidity control range	45%-95%
Working Temperature Range	5~38°C
Compressor type	Rotary
Sound	45dB(decibel)
Drainage way	Water tank/water pump
Warranty	1 Year
Standard packaging	Wooden case
N.Weight	40kgs
Dimension(L*W*H)	413x531x831mm

FEATURES

- World famous brand compressor, 3 minutes delay protection
- Ambient humidity LCD display timely
- Humidity control set freely, accuracy to $\pm 3\%$
- Continuously drainage by external soft tube
- Automatic defrosting when the ambient temperature is below 18°C
- Timed shut down setting
- Humidity sensor malfunction alert
- High efficiency, energy saving
- Large rear wheels to adapt to various road conditions.
- Stainless steel handle, portable push-pull

TOJJE SERVICE

- 1.OEM/ODM orders welcomed, full sets drawings provide within 7 days
- 2.Precision solution and offer provide within 2 days, fastest response by kinds of communication way
- 3.One-to-one unique on-call customer service with 10 minutes reply rate
- 4.1 year warranty for whole unit, allow extend the warranty 2 year after discussion.
- 5.Supply spare parts for free if machine damaged because of quality defects.
- 6.Provide Ce certificates,quality assurance agreements,technical advice, installation guidance.



WORKING PRINCIPLE

The design purpose of the TOJJE DJ-581ET dehumidifier is to dehumidify the air entering the unit by entering the evaporator coil, in order to lower the air temperature below the dew point. Humidity is removed from the air and discharged from the outside of the device to public floors or waste discharge outlets. Then, the air overheats in the serpentine tube of the condenser and leaves the device. Dehumidification occurs before reaching the set value, and then closes until the control determines the necessary operation.

IMPLEMENT

The TOJJE DJ-581ET dehumidifier is the perfect solution for accurately adjusting the humidity required for indoor environments.

