



DESICCANT DEHUMIDIFIER

DZ-D-400M



- *Swedish Proflute runner, 10 years of continuous operation without failure
- *SCR constant temperature control technology, more stable operation for a long time
- *Low dew point dehumidification operation
- *PTC heating technology, significant energy saving effect
- *Stop protection mode, more secure to use
- *Intelligent control system, precise humidity control

Model number	DZ-D-400M
Dehumidifying capacity(20°C,60%)	2kg/hr
Supply Voltage	220V/50Hz、220V/60Hz
Process air flow	420m3/hr
Reactivation air flow	130m3/hr
Process air inlet	125mm
Dry air outlet	125mm
Regen.air inlet	80mm
Wet air outlet	80mm
Applied Temperature	-15°C-50°C
Max power	2.3KW
Power rating	2KW
Current	10A
Dimension	680*424*375mm
Package size	750*505*560mm
Weight	32kg



DESICCANT DEHUMIDIFIER



DZ-D-600M

- *Swedish Proflute runner, 10 years of continuous operation without failure
- *SCR constant temperature control technology, more stable operation for a long time
- *Low dew point dehumidification operation
- *PTC heating technology, significant energy saving effect
- *Stop protection mode, more secure to use
- *Intelligent control system, precise humidity control

Model number	DZ-D-600M
Dehumidifying capacity(20°C,60%)	3kg/hr
Supply Voltage	220V/50Hz、220V/60Hz
Process air flow	580m3/hr
Reactivation air flow	200m3/hr
Process air inlet	125mm
Dry air outlet	125mm
Regen.air inlet	100mm
Wet air outlet	100mm
Applied Temperature	-15°C-50°C
Max power	4.5KW
Power rating	3.8KW
Current	20A
Dimension	585*415*860mm
Package size	685*505*1040mm
Weight	55kg



DZ-D-700M



- *Swedish Proflute runner, 10 years of continuous operation without failure
- *SCR constant temperature control technology, more stable operation for a long time
- *Low dew point dehumidification operation
- *PTC heating technology, significant energy saving effect
- *Stop protection mode, more secure to use
- *Intelligent control system, precise humidity control

Model number	DZ-D-700M
Dehumidifying capacity(20°C,60%)	3.5kg/hr
Supply Voltage	380V/50Hz
Process air flow	650m3/hr
Reactivation air flow	250m3/hr
Process air inlet	200mm
Dry air outlet	200mm
Regen.air inlet	125mm
Wet air outlet	125mm
Applied Temperature	-15°C-50°C
Max power	6.4KW
Power rating	6KW
Current	14A
Dimension	980*550*632mm
Package size	1160*620*800
Weight	85kg



DESICCANT DEHUMIDIFIER

DZ-D-1000M



- *Swedish Proflute runner, 10 years of continuous operation without failure
- *SCR constant temperature control technology, more stable operation for a long time
- *Low dew point dehumidification operation
- *PTC heating technology, significant energy saving effect
- *Stop protection mode, more secure to use
- *Intelligent control system, precise humidity control

Model number	DZ-D-1000M
Dehumidifying capacity(20°C,60%)	7.5kg/hr
Supply Voltage	380V/50Hz
Process air flow	1100m3/hr
Reactivation air flow	400m3/hr
Process air inlet	200mm
Dry air outlet	200mm
Regen.air inlet	150mm
Wet air outlet	150mm
Applied Temperature	-15°C-50°C
Max power	13KW
Power rating	10KW
Current	18A
Dimension	830*640*1220mm
Package size	960*715*1405mm
Weight	142kg



DESICCANT DEHUMIDIFIER



DZ-D-1200M/DZ-D-1500M

- *Swedish Proflute runner, 10 years of continuous operation without failure
- *SCR constant temperature control technology, more stable operation for a long time
- *Low dew point dehumidification operation
- *PTC heating technology, significant energy saving effect
- *Stop protection mode, more secure to use
- *Intelligent control system, precise humidity control

Model number	DZ-D-1200M	DZ-D-1500M
Dehumidifying capacity(20°C,60%)	8.5kg/hr	10kg/hr
Supply Voltage	380V/50Hz	380V/50Hz
Process air flow	1250m3/hr	1550m3/hr
Reactivation air flow	450m3/hr	580m3/hr
Process air inlet	250mm	250mm
Dry air outlet	250mm	250mm
Regen.air inlet	160mm	160mm
Wet air outlet	160mm	160mm
Applied Temperature	-15°C-50°C	-15°C-50°C
Max power	13.5KW	15KW
Power rating	11KW	13KW
Current	22A	26A
Dimension	970*750*1180mm	970*750*1180mm
Package size	990*800*1410mm	990*800*1410mm
Weight	155kg	157kg



DZ-D-2500M/DZ-D-3000M



- *Swedish Proflute runner, 10 years of continuous operation without failure
- *SCR constant temperature control technology, more stable operation for a long time
- *Low dew point dehumidification operation
- *PTC heating technology, significant energy saving effect
- *Stop protection mode, more secure to use
- *Intelligent control system, precise humidity control

Model number	DZ-D-2500M	DZ-D-3000M
Dehumidifying capacity(20°C,60%)	15kg/hr	19kg/hr
Supply Voltage	380V/50Hz	380V/50Hz
Process air flow	2550m3/hr	3000m3/hr
Reactivation air flow	925m3/hr	1100m3/hr
Process air inlet	400mm	400mm
Dry air outlet	450*225mm	450*225mm
Regen.air inlet	200mm	200mm
Wet air outlet	200mm	200mm
Applied Temperature	-15°C-50°C	-15°C-50°C
Max power	24KW	30KW
Power rating	22KW	27KW
Current	50A	60A
Dimension	1295*880*1300mm	1295*880*1300mm
Package size	1395*935*1470mm	1395*935*1470mm
Weight	295kg	300kg